



TECHNICAL DATA

GB CALIBRATION FLUID 4113

A calibration and storage oil for diesel fuel injectors

APPLICATIONS

GB CALIBRATION FLUID 4113 has been specially developed for use as a calibration and storage oil for diesel fuel injectors.

PERFORMANCE FEATURES

GB CALIBRATION FLUID 4113 is formulated with rust preventative properties, so that without cleaning the equipment after calibration, proper functioning is maintained for up to one year's storage.

PERFORMANCE DETAILS

GB CALIBRATION FLUID 4113 may be used where the following specifications are required:

| | |
|----------|--------------------|
| ISO 4113 | LUCAS CAV 7-10-106 |
|----------|--------------------|

CHARACTERISTICS

| TEST | UNIT | TYPICAL PHYSICAL CHARACTERISTICS |
|---------------------------------------|-------------------|--|
| Density @ 15°C | Kg/m ³ | 825 |
| Kinematic Viscosity @ 40°C | cSt | 2.45 – 2.60 |
| Flash Point (Open) | °C | 110 |
| Rust Prevention (ASTM D1748:50 hours) | | Pass for five out of six faces on three panels |

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
 Tel: 0191 490 4312
 Fax: 0191 477 9544
 e-mail: gblsales@gb-lubricants-fuels.co.uk
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB CALIBRATION FLUID 4113 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB CALIBRATION FLUID 4113 is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS173.0207.03