



# TECHNICAL DATA

## GB CALIBRATION FLUID TYPE C

### APPLICATIONS

GB CALIBRATION FLUID TYPE C has been specifically formulated for use in diesel injector calibration equipment requiring a product meeting the Lucas specification CAV 70-10-100.

### PERFORMANCE FEATURES

GB CALIBRATION FLUID TYPE C is formulated from specially selected, highly refined mineral oils and additives to be blended to the very close viscosity limits required for diesel injector calibration equipment.

### PERFORMANCE DETAILS

GB CALIBRATION FLUID TYPE C may be used where the following specification is required:

LUCAS CAV 70-10-100
---------------------

### CHARACTERISTICS

TEST	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	Clear colourless liquid
Density @ 20°C	840
Kinematic Viscosity @ 21°C, cSt	6.70
Pour Point °C	-21
Flash Point °C (PMCC)	126

### STORAGE AND HANDLING

GB CALIBRATION FLUID TYPE C should be stored under cover to avoid water collecting in the rim of upturned barrels.

Cont'd./...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: [gblsales@gb-lubricants-fuels.co.uk](mailto:gblsales@gb-lubricants-fuels.co.uk)

[www.gb-lubricants-fuels.co.uk](http://www.gb-lubricants-fuels.co.uk)

A division of Goodall Bates & Todd Ltd



Q 06093  
ISO 9001



EMS 72776  
ISO 14001



OHS 88475  
OHSAS 18001

### **HEALTH, SAFETY AND THE ENVIRONMENT**

Further information on GB CALIBRATION FLUID TYPE C can be obtained by referring to the corresponding Material Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, [www.environment-agency.gov.uk](http://www.environment-agency.gov.uk), as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS192.0409.03