



TECHNICAL DATA

GB DETERGENT FLUSHING OIL

A detergent flushing oil for use in petrol and diesel engines

APPLICATIONS

GB DETERGENT FLUSHING OIL has been developed using the highest quality mineral virgin base oils and multifunctional additives to penetrate every part of the engine, dissolving and draining contaminants that are not normally removed by routine draining.

DIRECTIONS FOR USE

- The oil, whilst warm, should be drained in the normal way and the sump drain plug replaced.
- GB DETERGENT FLUSHING OIL should then be added to the normal sump capacity.
- Start the engine and idle at low revolutions for 15 minutes, with occasional bursts at higher revolutions.
- Stop the engine, drain in the normal way and replace the sump drain plug. If the oil appears very dirty, it is advisable to repeat the process with new GB DETERGENT FLUSHING OIL.
- Renew the oil filter or clean external oil filter, whichever is applicable.
- Refill with the correct grade of GB Lubricants Ltd engine oil.

NB: The vehicle should not be driven on the road containing only GB DETERGENT FLUSHING OIL as the lubricant.

GB DETERGENT FLUSHING OIL should not be used on Leyland engines with automatic gearboxes contained in the sump, or automatic transmissions.

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Density @ 15°C	kg/m ³	IP 160	866
Kinematic Viscosity @ 40°C	cSt	IP 71	15.5

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
 Tel: 0191 490 4312
 Fax: 0191 477 9544
 e-mail: gblsales@gb-lubricants-fuels.co.uk
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB DETERGENT FLUSHING OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB DETERGENT FLUSHING OIL is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS72.0207.05