



TECHNICAL DATA

GB F11 WATER DISPLACER

APPLICATIONS

GB F11 WATER DISPLACER is a premium water-displacing rust preventative and penetrating fluid. It will rapidly displace water from metal surfaces in general maintenance, after machining operations or alkali cleaning. It provides highly effective protection from atmospheric corrosion, even under conditions of high humidity and is also a very effective penetrating fluid.

GB F11 WATER DISPLACER is particularly recommended as a general-purpose corrosion protective, which is non-staining and suitable for indoor storage conditions.

PERFORMANCE FEATURES

GB F11 WATER DISPLACER has been developed to provide the following features:

- A non-staining product
- Rapid separation of water from metal surfaces
- Protection of both ferrous and non-ferrous metals
- Suitability for high humidity environments
- General lubrication properties
- Good penetrating properties
- Easily removable with warm alkali detergents

APPLICATION METHOD

GB F11 WATER DISPLACER can be applied by spray, brush or dipping.

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

GB F11 WATER DISPLACER

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Amber Liquid
Odour	-	-	Slight
Kinematic Viscosity @ 40°C	cSt	IP 71	1.5
Autoflammability	°C	-	>290
Humidity Cabinet on Polished Steel Panels: Days to Fail	-	ASTM D3748	30+
Water Displacement	-	IP 178/81	Pass
Indoor Protection on Polished Steel Panels	Years	-	>2
Low Temperature Adhesion	°C	-	-30

STORAGE AND HANDLING

GB F11 WATER DISPLACER should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB F11 WATER DISPLACER is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS14.0207.08