



TECHNICAL DATA

GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE

APPLICATIONS

GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE is an additive package that has been developed specifically to improve the quality of diesel fuel and to enhance its performance.

PERFORMANCE FEATURES

GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE has been formulated with a variety of selected additives and offers the following features:

- Effective fuel detergency
- Improved cetane number
- Improved lubricity
- Foam control
- Corrosion control
- Water demulsification
- Oxidation stability
- Acceptable lubricant interaction

Reference should be made to the ancillary technical summary for detailed test results.

DILUTION

The treatment rate of GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE is approximately 1 litre to every 500 litres of product to be treated.

The container should be shaken before use and only added to the product to be treated at or above 5°C.

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Clear amber liquid
Density @ 15°C	kg/m ³	IP 160	906
Flash Point	°C	IP 34	63

STORAGE AND HANDLING

GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB MULTIFUNCTIONAL DIESEL FUEL ADDITIVE is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS74.0207.05