



# TECHNICAL DATA

## GB PENETRATING OIL

### APPLICATIONS

GB PENETRATING OIL has been developed using the highest quality mineral virgin base oils and selected additives for use as a penetrating fluid.

### PERFORMANCE FEATURES

GB PENETRATING OIL offers the following features:

- Release of rust-bound components
- Dust-removal and protection
- Maintenance of properties in damp conditions
- A non-staining product

### CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Density @ 15°C	kg/m <sup>3</sup>	IP 160	828
Kinematic Viscosity @ 40°C	cSt	IP 71	4.0

### STORAGE AND HANDLING

GB PENETRATING OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

Cont'd.../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP  
Tel: 0191 490 4312  
Fax: 0191 477 9544  
e-mail: [gblsales@gb-lubricants-fuels.co.uk](mailto:gblsales@gb-lubricants-fuels.co.uk)  
[www.gb-lubricants-fuels.co.uk](http://www.gb-lubricants-fuels.co.uk)

A division of Goodall Bates & Todd Ltd



Q 06093  
ISO 9001



EMS 72776  
ISO 14001



OHS 88475  
OHSAS 18001

# GB LUBRICANTS

**HEALTH, SAFETY AND THE ENVIRONMENT**

GB PENETRATING OIL is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, [www.environment-agency.gov.uk](http://www.environment-agency.gov.uk), as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS196.0207.02