GB SOLVENT CLEANER

An emulsifiable diphase solvent degreaser

APPLICATIONS

GB SOLVENT CLEANER has been developed using hydrocarbon solvents and emulsifiers to quickly penetrate dirty oily deposits on the surfaces of machinery, vehicles, floors, paintwork etc, which can then be flushed clean with cold water.

PERFORMANCE FEATURES

GB SOLVENT CLEANER is formulated to offer the following features:

- Application by spraying, dipping, soaking or brushing
- It wets the surface with a continuous film of solvent
- The ability to wet, penetrate and solubilise dirty oily deposits
- Cost effectiveness

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Clear Fluid
Density @ 15°C	kg/m^3	IP 160	803
Kinematic Viscosity @ 40°C	cSt	IP 71	1.7

Cont'd .../...

GB LUBRICANTS
Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk
A division of Goodall Bates & Todd Ltd

STORAGE AND HANDLING

GB SOLVENT CLEANER should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB SOLVENT CLEANER is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.