



TECHNICAL DATA

GB TRAFFIC FILM REMOVER

An alkaline liquid traffic soil remover

APPLICATIONS

GB TRAFFIC FILM REMOVER has been developed using a blend of alkaline builders and biodegradable surfactants, for the regular brushless valeting of painted surfaces by hot or cold pressure washing machines, to remove road dirt and traffic film.

PERFORMANCE FEATURES

GB TRAFFIC FILM REMOVER is formulated to offer the following features:

- Suitability for application with a wide range of automatic vehicle washing machines
- A continuous film of solvent to wet surfaces
- The ability to wet, penetrate and solubilise dirty oily deposits

DILUTION

GB TRAFFIC FILM REMOVER has a treatment rate of between 0.5% and 4.0% when added to water, depending on the method of application and nature of the cleaning operation.

MATERIAL COMPATIBILITY

When GB TRAFFIC FILM REMOVER is used in the recommended manner, no corrosion is likely on mild steel or brass. However, use on a combination of mild steel and brass will cause corrosion. GB TRAFFIC FILM REMOVER will attack zinc, aluminium and their alloys; some aluminium alloys may develop a green/black discolouration.

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

GB TRAFFIC FILM REMOVER

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Green
Density at 15°C	Kg/m ³	IP 160	1019
Flash Point			Non Flammable

STORAGE AND HANDLING

GB TRAFFIC FILM REMOVER should be protected from freezing temperatures and stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB TRAFFIC FILM REMOVER is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS98.0207.05