



TECHNICAL DATA

GB UNIVERSAL ANTIFREEZE

A premium quality engine coolant and antifreeze.

APPLICATIONS

GB UNIVERSAL ANTIFREEZE has been developed to protect most types of car, motorbike, heavy goods and passenger service vehicle engines against corrosion and frost damage.

PERFORMANCE FEATURES

GB UNIVERSAL ANTIFREEZE is formulated on monoethylene glycol and contains a blend of inhibitors which give a high degree of corrosion protection to all parts of both petrol and diesel engine cooling systems.

GB UNIVERSAL ANTIFREEZE, which contains no methanol and is phosphate free, may be used where the specification BS 6580:1992 is required.

Because of the stability of the inhibitor used, GB UNIVERSAL ANTIFREEZE is suitable for all year round use, although a new charge is recommended at the start of each winter.

DILUTION

CONCENTRATION		PROTECTION
33%	1 part GB UNIVERSAL ANTIFREEZE to 2 parts water	-18°C
50%	1 part GB UNIVERSAL ANTIFREEZE to 1 part water	-33°C

Most antifreeze blends are based on carefully balanced mixtures of various anti-corrosion inhibitors. The mixing of different antifreezes can lead to loss of corrosion protection. GB Lubricants Limited does not therefore recommend mixing different blends of antifreeze.

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Colour			Blue
Density at 15°C	Kg/m ³	IP 160	1.125

STORAGE AND HANDLING

GB UNIVERSAL ANTIFREEZE should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB UNIVERSAL ANTIFREEZE is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.