



TECHNICAL DATA

GB UNIVERSAL BRAKE FLUID 260D4

A premium synthetic brake and clutch fluid

APPLICATIONS

GB UNIVERSAL BRAKE FLUID 260D4 is a premium synthetic brake and clutch fluid developed for use in cars, commercial vehicles and motorbikes. It should not be used in some Citroen cars or vehicles requiring a mineral oil.

PERFORMANCE FEATURES

GB UNIVERSAL BRAKE FLUID 260D4 is formulated to obtain optimum performance and to provide maximum safety and offers the following features:

- High boiling point and low vapour pressure
- Compatibility with rubber
- Good lubrication
- Long-term stability
- Fluidity at low temperatures
- Miscibility with other approved commercial products
- Maintained viscosity over a wide temperature range
- Compatibility with metals

PERFORMANCE DETAILS

GB UNIVERSAL BRAKE FLUID 260D4 may be used where the following specifications are required:

FMVSS 116 DOT 4 FMVSS 116 DOT 3	SAE J 1703 ISO 4925
------------------------------------	------------------------

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHODS	TYPICAL PHYSICAL CHARACTERISTICS
Colour			Pale Amber
Density @ 20°C	kg/m ³		1039
Kinematic Viscosity @ -40°C	cSt	ASTM D445	1351
Equilibrium Reflux Boiling Point	°C	FMVSS 116	269
Wet Equilibrium Boiling Point	°C	FMVSS 116	159

SPECIAL HANDLING PRECAUTIONS

As brake fluid absorbs moisture the container closure should always be replaced immediately after use. When filling a brake system, never use any vessel or funnel contaminated with dirt, mineral oil, petrol, paraffin or water. If spilt on paintwork, brake fluid may cause damage. Therefore, any spillage should be washed off immediately with water.

STORAGE AND HANDLING

GB UNIVERSAL BRAKE FLUID 260D4 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB UNIVERSAL BRAKE FLUID 260D4 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.