



TECHNICAL DATA

GB TURBO SXV 5W-30

APPLICATIONS

GB TURBO SXV 5W-30 is a fully synthetic passenger car oil formulated using the highest quality synthetic base oils and enhanced additive systems for use in both petrol and diesel engines. It has been specifically engineered for all General Motors cars requiring a product meeting GM-LL-A-025 or GM-LL-B-025 and, because of its lower viscosity, it is recognised as a fuel-efficient lubricant which also provides better cold starting and less wear on engines, starter motors and batteries. Although specifically engineered for General Motors, it may also be used in vehicles manufactured by other OEM's when the performance and viscosity grade are applicable.

PERFORMANCE FEATURES

GB TURBO SXV 5W-30 has been developed for General Motors cars and also as a fuel-efficient lubricant and offers the following features:

- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability
- Improved fuel economy
- Exceptional shear stability

PERFORMANCE DETAILS

GB TURBO SXV 5W-30 may be used where the following specifications are required:

ACEA A3/B4 API SL/CF	GM-LL-A-025 GM-LL-B-025	MERCEDES BENZ p229.5 VW 502/505
-------------------------	----------------------------	------------------------------------

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			5W-30
Appearance	-	-	Clear amber liquid
Kinematic Viscosity @ 100°C	cSt	IP 71	12.0
Kinematic Viscosity @ 40°C	cSt	IP 71	70.0
Viscosity Index	-	IP 226	171
Density	kg/m ³	IP 160	855
CCS @ -30°C	cP	ASTM D 5293	5960
Flash Point	°C	IP 36	240
Pour Point	°C	IP 15	-36

STORAGE AND HANDLING

GB TURBO SXV 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

Further information on GB TURBO SXV 5W-30 can be obtained by referring to the corresponding Material Safety Data Sheet.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.