



TECHNICAL DATA

GB TURBO X 15W-50

APPLICATIONS

GB TURBO X 15W-50 is formulated using the highest quality virgin mineral base oils and enhanced additive systems for use in both petrol and diesel passenger car engines. These include high-performance, turbo-charged passenger cars as well as naturally aspirated models; it may also be used in light trucks and vans.

PERFORMANCE FEATURES

GB TURBO X 15W-50 has been developed for high performance passenger cars and offers the following features:

- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability

PERFORMANCE DETAILS

At the viscosity of 15W-40, the following performance claims have been met:

ACEA A3/B3 API SL/CF	MERCEDES BENZ p227.1/229.1 VW 505 00
-------------------------	---

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			15W-50
Appearance	-	-	Clear amber liquid
Kinematic Viscosity @ 100°C	cSt	-	18.0
Kinematic Viscosity @ 40°C	cSt	-	137.2
Viscosity Index	-	-	146
Density	kg/m ³	-	883
CCS @ -20°C	cP	-	6180
HTHS @ 150°C	mPa.s	-	4.53
Noack	%	-	10.9
KO AftVisc	cSt	-	16.61
KO % ShLoss	%	-	7.59
L38 AftVisc	cSt	-	16.90
L38 % ShLoss	%	-	5.97
Flash Point	°C	IP 34	210
Pour Point	°C	IP 15	-27

STORAGE AND HANDLING

GB TURBO X 15W-50 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB TURBO X 15W-50 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.