



TECHNICAL DATA

GB GERION® TS RANGE

APPLICATIONS

The GB GERION® TS RANGE has been developed using the highest quality virgin mineral base oils and advanced additive systems, for use in final drives and axles requiring an API GL-5 level of performance. It may also be used in gearboxes, when specified by Original Equipment Manufacturers.

PERFORMANCE FEATURES

The GB GERION® TS RANGE is formulated to satisfy the higher performance demands of today's drivetrain lubricants and offers the following features:

- Thermal stability
- Oxidation stability
- Anti-wear performance
- Corrosion protection
- Load-carrying properties
- Low foaming

PERFORMANCE DETAILS

The following specifications and the requirements of equipment manufacturers, such as those listed below, are met or exceeded:

API GL-5	VOLVO	FORD	OPEL
MIL-L-2105D	SCANIA	GENERAL MOTORS	PSA
MERCEDES BENZ	RVI	ROCKWELL	RENAULT
ZF	MAN	IVECO	FIAT
VAG	EATON	DAF	

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS			
			75W-80	80W-90	85W-90	85W-140
SAE						
Density @15°C	kg/m ³	IP 160	875	899	905	905
Kinematic Viscosity @40°C	cSt	IP 71	52.7	149.0	147.4	363.7
Kinematic Viscosity @100°C	cSt	IP 71	9.6	15.3	14.6	26.6
Viscosity Index	-	IP 226	164	106	98	98
Brookfield Viscosity @ -12°C	cP	ASTM D2983	-	-	130,000	40,250
Brookfield Viscosity @ -26°C	cP	ASTM D2983	-	123,100	-	-
Brookfield Viscosity @ -40°C	cP	ASTM D2983	57,000	-	-	-
Flash Point	°C	IP 34	160	172	162	204
Pour Point	°C	IP 15	-48	-33	-30	-21

STORAGE AND HANDLING

The GB GERION® TS RANGE should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

The GB GERION® TS RANGE is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.