



TECHNICAL DATA

GB REAR AXLE OIL PWB 10W-30

A premium wet brake fluid

APPLICATIONS

GB REAR AXLE OIL PWB 10W-30 has been developed using the highest quality mineral base oils and multifunctional additives, for use in wet brakes where squawk has developed.

PERFORMANCE FEATURES

GB REAR AXLE OIL PWB 10W-30 is specifically formulated to overcome the problem of squawk and offers the following features:

- Excellent squawk reduction
- Excellent gear wear protection
- Good brake chatter control
- Improved oxidation stability
- Increased gear loading
- Excellent low temperature performance

PERFORMANCE DETAILS

GB REAR AXLE OIL PWB 10W-30 may be used where the following specifications are required:

FORD M2C86-B/C	RENAULT
MASSEY FERGUSON M1135,M1141	DEUTZ
JOHN DEERE J20C	FIAT
CASE MS 1206/7/9	SAME
API GL-4 (CRC L20)	LANDINI
CATERPILLAR TO-2	FENDT

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			10W-30
Appearance			Clear amber liquid
Density at 15°C	kg/m ³	IP 160	870
Kinematic Viscosity @ 40°C	cSt	IP 71	64.0
Kinematic Viscosity @ 100°C	cSt	IP 71	10.0
Viscosity Index		IP 226	143
Brookfield Viscosity @ -18°C	cP	ASTM D2983	3650
Pour Point	°C	IP 15	-30
Flash Point	°C	IP 34	190

STORAGE AND HANDLING

GB REAR AXLE OIL PWB 10W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB REAR AXLE OIL PWB 10W-30 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.