



TECHNICAL DATA

GB KT MOULD OIL

APPLICATIONS

GB KT MOULD OIL has been formulated using the highest quality mineral virgin base oils and a specially selected reactive additive, to form a release layer between the setting concrete and the mould. It is particularly suited for fast moving production industries, where time constraints apply.

PERFORMANCE FEATURES

GB KT MOULD OIL offers the following features:

- Suitable for use on a wide range of mould materials
- Ideal for use on large surface areas
- Provides a superior surface finish
- Provides a clean release
- Good wetting-out properties

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance	-	-	Pale yellow liquid
Density @ 15°C	kg/m ³	IP 160	834
Kinematic Viscosity @ 40°C	cSt	IP 71	5.0
Flash Point	°C	IP 34	57

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
 Tel: 0191 490 4312
 Fax: 0191 477 9544
 e-mail: gblsales@gb-lubricants-fuels.co.uk
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB KT MOULD OIL should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH AND SAFETY AND THE ENVIRONMENT

GB KT MOULD OIL is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS218.0207.02