



TECHNICAL DATA

GB MOULD OIL CONCENTRATE

A concentrate for dilution with gas oil or paraffin

APPLICATIONS

GB MOULD OIL CONCENTRATE has been formulated with neat oils and surfactants, for dilution at the appropriate rate, according to the application for which it will be used. It is particularly suited for continuous processes, such as brick or tile manufacturing, or as a concrete mould release fluid.

PERFORMANCE FEATURES

GB MOULD OIL CONCENTRATE has been developed to provide variable dilution rates and offers the following features:

- An idea product for structural and textured work
- Suitability for use with hardwoods, sealed surfaces, steels and other metals, plastics, glassfibre etc
- Easy application by spray
- Dilution rates of 50% - 95%
- Economy of use

NB: GB MOULD OIL CONCENTRATE is not recommended for softwood or unsealed surfaces and should not be applied neat.

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Amber Liquid
Density at 15°C	kg/m ³	IP 160	893
Kinematic Viscosity at 40°C	cSt	IP 71	31.0

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB MOULD OIL CONCENTRATE should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH AND SAFETY AND THE ENVIRONMENT

GB MOULD OIL CONCENTRATE is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.