



TECHNICAL DATA

GB UNICUT® 11

A very low viscosity, high lubricity neat cutting oil

APPLICATIONS

GB UNICUT® 11 is a very low viscosity, neat cutting oil, based on the highest quality mineral virgin base oils and lubricity additives. It is a clear pale straw colour, does not stain yellow metals, such as brass or copper and is extremely acceptable to operators because of its low odour and pale colour.

GB UNICUT® 11 was specially developed as a blanking fluid but it is also suitable for cutting operations that require a good flushing action, good lubricity and heat removal.

PERFORMANCE FEATURES

Special features of GB UNICUT® 11 are:

- Its high quality mineral virgin basestock
- Its very low viscosity
- Its high lubricity level
- Its low vapour production
- It is non-staining towards yellow metals

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Pale yellow
Density @ 15°C	kg/m ³	IP 160	804
Kinematic Viscosity @ 40°C	cSt	IP 71	1.5
Flash Point	°C	IP 34	58

Cont'd.../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
 Tel: 0191 490 4312
 Fax: 0191 477 9544
 e-mail: gblsales@gb-lubricants-fuels.co.uk
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB UNICUT® 11 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB UNICUT® 11 is classified as hazardous under current UK Health & Safety and Environmental Legislation and should only be used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.

TDS191.0207.04